

# Zep S-20

## 20" AUTO SCRUBBER

**COST EFFECTIVE. HIGHLY EFFICIENT.**

Industrial strength and performance make this auto scrubber perfect for your toughest cleaning challenges. Combine that with a budget pleasing price and it is the solution for your floor maintenance programs.

- A** Training graphics are on the control panel. New or experienced operators learn as easy as 1, 2, 3!
- B** Clean on your schedule with sound levels down to 63 dBA
- C** Transport the machine without worry with frame and tank tie down points
- D** Don't kneel or strain your back again with automatic on/off brush system



### APPLICATIONS:

The Zep S-20, available as pad assist or traction drive rotary disk auto scrubber is for:

- Daily scrubbing & project work (deep scrub or strip jobs) of smaller facilities
- Dedicated facility or multi-facility route cleaning programs
- Small rooms, detail & edge cleaning in larger facilities
- Grout and porous floor scrubbing
- Entry-ways & lobbies
- Check-out aisles
- Spill clean-up & water recovery



*Superior Solutions*

# SCRUBBER SPECIFICATIONS

	<b>Zep S-20 Pad Assist</b>	<b>Zep S-20 Traction</b>
	FC00603 w/wet batt & on-board chgr. FC00689 w/MF batt & on-board chgr. FC00690 no batt & on-board chgr.	FC00604 w/wet batt & on-board chgr. FC00635 w/MF batt & on-board chgr. FC00632 no batt & on-board chgr.
<b>SOLUTION DELIVERY SYSTEM</b>		
Solution capacity:	11 gal	11 gal
Solution control:	0-.5 gpm, variable, knob adjustment	0-.5 gpm, variable, knob adjustment
<b>SCRUBBING SYSTEM</b>		
Cleaning path:	20 in	20 in
Pad/brush size:	(1) 20 in	(1) 20 in
Productivity (per hour)-Theoretical max:	23,800 ft <sup>2</sup>	23,800 ft <sup>2</sup>
Productivity (per hour)-Average coverage rate*:	10,630 ft <sup>2</sup>	14,175 ft <sup>2</sup>
<b>BRUSH DRIVE SYSTEM</b>		
Brush motor horsepower:	.75 hp	.75 hp
Brush rpm:	230 rpm	230 rpm
Brush/pad pressure:	60 & 90 lb	60 & 90 lb
Brush/pad attachment/removal:	Auto on/off	Auto on/off
<b>RECOVERY SYSTEM</b>		
Recovery tank accessibility:	Full clean out access	Full clean out access
Recovery tank capacity:	13 gal (2 gal demisting chamber)	13 gal (2 gal demisting chamber)
Vacuum motor:	.51 hp, 2-stage	.51 hp, 2-stage
Vac motor cfm:	68 cfm	68 cfm
Squeegee width:	30 in	30 in
<b>DRIVE SYSTEM</b>		
Drive type:	Pad assist	Traction
Motor horsepower:	NA	.25 hp
<b>BATTERY SYSTEM</b>		
System voltage:	24 V	24 V
Battery amp hour rating:	130 AH (wet) / 105 AH (MF)	155 AH (wet) / 140 AH (MF)
Battery run time:	Up to 3 hours	Up to 3.5 hours
Charger description:	On-board	On-board
<b>MACHINE SPECIFICATIONS</b>		
Product length:	50 in	50 in
Product width (without squeegee):	21 in	21 in
Product height:	43 in	43 in
Product weight (with batteries):	380 lb	380 lb
Sound level (operator's ear):	63 dBA	63 dBA
Construction:	Rotationally molded polyethylene tanks, powder coated steel frame	Rotationally molded polyethylene tanks, powder coated steel frame
<b>WARRANTY</b>		
Rotationally-molded tanks:	10 years	10 years
Parts (excluding wear items):	3 years	3 years
Labor:	1 year	1 year
<b>OPTIONAL ACCESSORIES</b>		
Available accessories:	<b>Brushes</b> FC00679 scrub-poly FC00680 scrub-nylon FC00681 scrub-grit  <b>Pad Driver</b> FC00682  <b>FC00691 Parking Brake</b>  <b>FC00692 Digital Hour Meter**</b>	<b>Pads-Case of 5, 20 in</b> FC00683 black, stripping FC00684 blue, scrubbing FC00685 red, buffing & cleaning FC00686 white, buffing  <b>Squeegee Blades, Urethane</b> FC00687 front FC00688 rear  <b>FC00693 HydroLink Battery Watering System</b>

\*Productivity calculations utilize key factors from the ISSA 540 cleaning times handbook

\*\*Optional

Note: Specifications subject to change without notice

PURPOSE BUILT.™ BY



Superior Solutions

Zep Sales & Service, a unit of Zep Inc.  
Call 1-877-I BUY ZEP (1-877-428-9937) • www.zep.com